

# FL-BS01



www.fulbat.com - @ FULBAT







The FL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

## **DIMENSIONS & WEIGHT**

LENGHT	217 ±1mm
WIDTH	84.74 ±1mm
HEIGHT	58.30 ±2mm
WEIGHT DOOK (L. L	
WEIGHT	<b>0.96Kg</b> (tolerance ±3%)



- COMPATIBLE BATTERY TYPE
- HIGH CYCLE LIFE: UP TO 500 CYCLES
- LONG BATTERY LIFE: CAPACITY SOMETIMES HIGHER THAN THE ORIGINAL BATTERY
- HIGH QUALITY LITHIUM CELLS (LG, SAMSUNG, PANASONIC,...)
- MORE THAN 200 MODELS OF ROBOTS COVERED

SPECIFICATIONS	
Nominal voltage	32.4V (18650 - 9S2P)
Nominal capacity	3.0Ah
Energy	97.2Wh
Technology	Lithium-ion
Brand cells	Samsung
Protection function (PCM)	Over charge protection/Over discharge pro- tection/Over current protection/Tempera- ture protection/Balanced function
Standard charge	
Max charge Current	3A (37.8V max)
Standard discharge Standard discharge current Max discharge current	O.6A (cut-off voltage: 27V) 3A
Operating temp. range	
Charge temperature	0°C to 45°C
Discharge temperature	-10°C to 60°C 0°C to 40°C
Storage temperature	U LU 4U L



## **TERMINAL**



### **APPLICATIONS**



Mowe



#### **COMPATIBILITY (LIST NOT EXHAUSTIVE)**

BOSCH

INDIGO 800/850/1000/1100 CONNECT/1700 CONNECT/1300/3600/10C/13C

