DATA SHEET

FL-HU04



www.fulbat.com - @ FULBAT







The FL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.



LENGHT	146.26 ±1mm
WIDTH	67.66 ±1mm
HEIGHT	38.80 ±2mm
WFIGHT 0.49Km (tolerance ±3%)	
L MEIPHI	0.49Kg (tolerance ±3%)



- COMPATIBLE BATTERY TYPE
- HIGH CYCLE LIFE: UP TO 500 CYCLES
- Long Battery Life: Capacity Sometimes Higher Than The Original Battery
- HIGH QUALITY LITHIUM CELLS (LG, SAMSUNG, PANASONIC,...)
- MORE THAN 200 MODELS OF ROBOTS COVERED

SPECIFICATIONS	
OI LOII IONI IONO	
Nominal voltage	18V (18650 - 5S2P)
Nominal capacity	5.2Ah
Energy	93.6Wh
Technology	Lithium-ion
Brand cells	-
Protection function (PCM)	Over charge protection/Over discharge protection/Over current protection/Temperature protection/Balanced function
Standard charge	
Max charge Current	4A (2IV max)
Standard discharge Standard discharge current	0.8A (cut-off voltage: 15V)
Max discharge current	4A
Operating temp. range Charge temperature Discharge temperature Storage temperature	0°C to 45°C -10°C to 60°C 0°C to 40°C



TERMINAL



APPLICATIONS



Mowe



HUSQVARNA

AUTOMOWER 430X, 440, 450X

