

LITHIUM

The FL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

DIMENSIONS & WEIGHT

LENGTH	212.70 ±1mm
WIDTH	53 ±1mm
HEIGHT	74.90 ±2mm
WEIGHT	1.47Kg (tolerance ±3%)


FEATURES

- COMPATIBLE BATTERY TYPE
- HIGH CYCLE LIFE: UP TO 500 CYCLES
- LONG BATTERY LIFE: CAPACITY SOMETIMES HIGHER THAN THE ORIGINAL BATTERY
- HIGH QUALITY LITHIUM CELLS (LG, SAMSUNG, PANASONIC,...)
- MORE THAN 200 MODELS OF ROBOTS COVERED

SPECIFICATIONS

Nominal voltage	25.6V (26650 - 8S2P)
Nominal capacity	6.0Ah
Energy	153.6Wh
Technology	LiFePO4
Brand cells	-
Protection function (PCM)	Over charge protection/Over discharge protection/Over current protection/Temperature protection/Balanced function
Standard charge	
Max charge Current	6A (29.2V max)
Standard discharge	
Standard discharge current	1.2A (cut-off voltage: 16V)
Max discharge current	30A
Operating temp. range	
Charge temperature	0°C to 45°C
Discharge temperature	-10°C to 60°C
Storage temperature	0°C to 40°C

TERMINAL



APPLICATIONS



Robot Mower

COMPATIBILITY (LIST NOT EXHAUSTIVE)

- ROBOMOW**
RS612/RS622/RS635, RS1000/RS1800/RS3000
- WOLF GARTEN**
RS1000/RS1800/RS3000
- CUB CADET**
3000