


FL-ST01



www.fulbat.com - @ FULBAT







DIMENSIONS & WEIGHT

LENGHT	147.8 ±1mm
WIDTH	92.8 ±1mm
HEIGHT	64.5 ±2mm
WEIGHT AMEN () DO()	
I WFIGHT	1 15Kn (tolerance ±3%)



FEATURES

- COMPATIBLE BATTERY TYPE
- HIGH CYCLE LIFE: UP TO 500 CYCLES
- Long Battery Life: Capacity Sometimes Higher Than The Original Battery
- HIGH QUALITY LITHIUM CELLS (LG, SAMSUNG, PANASONIC,...)
- MORE THAN 200 MODELS OF ROBOTS COVERED

SPECIFICATIONS	
Nominal voltage	25.2V (18650 - 7S2P)
Nominal capacity	8.7Ah
Energy	219.24Wh
Technology	Lithium-ion
Brand cells	SAMSUNG - INR18650 - 29E
Protection function (PCM)	Over charge protection/Over discharge pro- tection/Over current protection/Tempera- ture protection/Balanced function
Standard charge	
Max charge Current	4.125A (29.4V max)
Standard discharge	
Standard discharge current	0.825A (cut-off voltage: 12.5V)
Max discharge current	15A
Operating temp. range	
Charge temperature	0°C to 45°C
Discharge temperature	-10°C to 60°C
Storage temperature	0°C to 40°C



TERMINAL







Mowe



COMPATIBILITY (LIST NOT EXHAUSTIVE)

- **AMBROGIO** Type Lido Serie
- STIGA AUTOCLIP 140/325/520

