DATA SHEET

FL-WX02



www.fulbat.com - 🛛 FULBAT







The FL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

DIMENSIONS & WEIGHT

I FNGHT	109.50 ±1mm	
WIDTH	74.70 ±1mm	
	0/00 0	
HEIGHT	64.20 ±2mm	
WEIGHT	0.58Kg (tolerance ±3%)	

FEATURES

- COMPATIBLE BATTERY TYPE
- HIGH CYCLE LIFE: UP TO 500 CYCLES
- LONG BATTERY LIFE: CAPACITY SOMETIMES HIGHER THAN THE ORIGINAL BATTERY
- HIGH QUALITY LITHIUM CELLS (LG, SAMSUNG, PANASONIC,...)
- MORE THAN 200 MODELS OF ROBOTS COVERED

SPECIFICATIONS	
Nominal voltage	20V (18650 - 5S2P)
Nominal capacity	5.0Ah
Energy	100.0Wh
Technology	Lithium-lon
Brand cells	Panasonic
Protection function (PCM)	Over charge protection/Over discharge pro- tection/Over current protection/Tempera- ture protection/Balanced function
Standard charge	
Max charge Current	5A (21V max)
Standard discharge Standard discharge current Max discharge current	1A (cut-off voltage: 15V) 5A
Operating temp. range Charge temperature	0°C to 45°C
Discharge temperature Storage temperature	-10°C to 60°C 0°C to 40°C

APPLICATIONS



MUWGI

COMPATIBILITY (LIST NOT EXHAUSTIVE)

• WORX

LANDROID L2000/M1000/M700

